



landis
INTERNATIONAL

Pneumatic Sole Press

Hercules Pneumatic Press Series

For Full Control of Bonding Pressure Applied for Perfect Cementing

Those unique machine makes a shoe press affordable for everyone. Due to the different types of synthetic materials being used in manufacturing today, it is essential to utilize a shoe press along with the proper adhesives to be able to meet the demands of today's market.

Specifications

Model HerculeSSS

- Dimensions: 406mm W x 1130mm H x 508mm D (16"x 44.5"x20")
- Net Weight: 65Kg (144 Lbs.)
- Crated Weight: 105Kg (230 Lbs.)

Model Hercule SSSD Double Press

- Dimensions: 432mm W x 1130mm H x 508mm D (17"x44.5x20)
- Net Weight: 93Kg (204 Lbs.)
- Crated Weight: 131Kg (289 Lbs.)

Did you know that with a pneumatic press you control the pressure applied to the bond?

The impact from a hammer can easily break bonds. Too much pressure will break the bonds!



SKU: HERCULESSD



SKU: HERCULESSS

The Hercules Pneumatic Press is the only one available that allows you to press shoe sole side down, as recommended when using super glues.

Standard Features on both models:

- Runs off air compressor (not included)
- Adjustable pressure control
- Adjustable speed control
- Quick hand lever for on/off
- Solid weld construction
- 305mm x 152mm (12"x 6") conforming sole cushion
- 152mm x 152mm (6" x 6") flat heel cushion
- 8 pair half sole lasts
- 2 heel lasts

Hercule SSSD Double Press

- Independent Adjustable pressure control
- 12" x 6" conforming sole cushion
- 6" x 6" flat heel cushion

Options on all models

- Full sole last kit
- Air compressor
- Birkenstock foot beds
- Orthotic heel post attachment with contoured pad